



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventorship.....Michail et al.
 Applicant..... Microsoft Corporation
 Attorney's Docket No. MS1-676US
 Title: Headlight Rendering Services Component For An Extensible Editor

TRANSMITTAL LETTER AND CERTIFICATE OF MAILING

To: Commissioner of Patents and Trademarks,
 Washington, D.C. 20231

From: James R. Banowsky (Tel. 509-324-9256; Fax 509-323-8979)
 Lee & Hayes, PLLC
 421 W. Riverside Avenue, Suite 500
 Spokane, WA 99201

The following enumerated items accompany this transmittal letter and are being submitted for the matter identified in the above caption.

1. Specification—title page, plus 54 pages, including 27 claims and Abstract
2. Transmittal letter including Certificate of Express Mailing
3. 7 Sheets Formal Drawings (Figs. 1-7)
4. Return Post Card

Large Entity Status [x]

Small Entity Status []

Date: 9/29/00

By:

James R. Banowsky
 James R. Banowsky
 Reg. No. 37,773

CERTIFICATE OF MAILING

I hereby certify that the items listed above as enclosed are being deposited with the U.S. Postal Service as either first class mail, or Express Mail if the blank for Express Mail No. is completed below, in an envelope addressed to The Commissioner of Patents and Trademarks, Washington, D.C. 20231, on the below-indicated date. Any Express Mail No. has also been marked on the listed items.

Express Mail No. (if applicable) EL685271453

Date: 9/29/2000

By:

Dana L. Calhoun
 Dana L. Calhoun



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

**Highlight Rendering Services Component For An
Extensible Editor**

Inventors:

Ashraf Michail

Mark Alcazar

John Bedworth

ATTORNEY'S DOCKET NO. MS1-676US

1 **TECHNICAL FIELD**

2 The systems and methods described herein relate to extensible editors and,
3 more particularly, the described implementations relate to highlight rendering
4 services in an extensible editor.
5

6 **BACKGROUND**

7 The process of editing electronic documents generally consists of
8 processing events and key combinations received by an editor. From events and
9 key combinations, an editing space is created. The editing space consists of a
10 document state plus a view state (visual feedback). The view state includes a
11 selection state (what is selected, what is shown as feedback), scroll position, etc.
12 The event interacts with the current state, and an editing model is applied to
13 manipulate feedback or to manipulate the document based on the feedback.

14 Extensible editors typically provide a set of document manipulation
15 services that can enable macros to perform advanced tasks on the content of a
16 document. With an extensible editor, developers can couple extensions that define
17 or re-define a manner in which the editor responds to events or key combinations
18 and provides visual feedback to a user. For example, if a developer wishes to
19 create a new look to a selection process or a highlighting process in an extensible
20 editor, the developer can create an extension that receives input regarding cursor
21 position, cursor movement, mouse actions, etc. The developer can design the
22 extension to use this input to create visual feedback that differs from a default
23 selection service or highlight service of the editor. However, familiar behavior of
24 the editor (such as clicking a “bold” button) is still retained by the editor. In
25

1 addition, an extension can also expose virtually any kind of functionality through
2 its own interfaces.

3 Extensible editors are designed so that one or more extensions can be
4 coupled with the editor. This is accomplished by implementing a set of interfaces
5 to which the extensions must conform. The interfaces are utilized by the
6 extensions to access a host of basic functions so that the extensions themselves are
7 not required to implement such basic functions. The extensions instead utilize the
8 basic functions to perform tasks that supplement or override functions performed
9 by the editor.

10 Extensible editors are desirable for their ability to include customer
11 extensions to provide a rich editing experience. A significant part of an editing
12 experience involves the highlight rendering model provided by the editor. A user
13 may wish to develop a custom extension that includes a highlight rendering
14 process that provides a unique look and feel to visual feedback that a user sees
15 during an editing session, but that does not actually change the content that is
16 being edited.

17 When utilizing extensions in an extensible editor, however, a conflict
18 problem can arise if multiple extensions are used simultaneously that act upon the
19 occurrence of the same event or key combination. If a first extension reacts to an
20 event in one way, but a second extension receives the event after the first extension
21 has acted on it, the second extension may also act on the event and, as a result,
22 override the action of the first extension. This problem can occur even when using
23 only one extension, if the extension acts on an event or key combination but does
24 not prevent the (default) editor from subsequently acting on the same event.

SUMMARY

An extensible editor for editing electronic documents and/or content is described herein. The extensible editor provides a highlight rendering services component that allows extensions to interface with the editor to provide custom visual feedback to a user during an editing session. Although the visuals are displayed to the user, the actual document content that is being edited is not altered. The editor can thereby implement the custom highlight rendering without having to be aware of details of how the highlight rendering process is implemented in the extension. The extensible editor ("editor") includes three sets of interfaces for extension integration.

The first set of interfaces is part of a designer extensibility mechanism. The designer extensibility mechanism is used to couple an extension (also called a "designer") to utilize the event routing model. The designer extensibility mechanism provides the ability to connect an editor extension that can modify editing behavior. An attached designer receives events and key combinations in a predefined order and uses the set of interfaces to create custom editing extensions.

The designer extensibility mechanism includes an edit designer interface that has four methods: translate accelerator, pre-handle event, post-handle event and post-event notify. The methods act as callback routines whenever an event occurs in the editing environment of the editor. When an event comes into the editor, the four methods intercept the event at different points of the editor's event handling process. The editor invokes the methods sequentially. If multiple designers are utilized, the editor invokes the current method on each designer sequentially, in the order in which the designers were registered with the editor.

1 If a designer acts on an event and wants to prevent any subsequent designer
2 (or the editor) from acting on the event, the designer "consumes" the event by
3 returning an appropriate signal to the editor. The designer returns a different
4 signal when subsequent processing is to continue on an event.

5 If an event is a key combinations (Ctrl-A, Alt-P, etc.) it first passes through
6 the "translate accelerator" method. This is done in the order that the designers
7 were added to the editor. If a key combination was entered, then the designer acts
8 upon the event and "consumes" the event so that subsequent designers or the
9 default editor cannot subsequently act upon the event.

10 The post-editor event notify method is an exception to the rule that
11 consumed events are not passed on to subsequent designers or the editor for
12 further processing. This method is always called on all designers, regardless of
13 whether, or when, an event is consumed. This allows each designer to clean up
14 any internal states that may be anticipating an event that is consumed before
15 reaching the designer.

16 The second set of interfaces is included in a selection services component
17 of the editor. The selection services component provides designers with the ability
18 to manage logical selections that are used by commands and other extensions, *i.e.*,
19 the ability to modify the logical selection state of the editor. As a result, all editing
20 commands and services will be able to interact with a custom selection model
21 without having detailed knowledge of the designer that is implementing the
22 selection.

23 The third set of interfaces is included in a highlight rendering services
24 component. The highlight rendering component allows a user to modify the
25 rendered character attributes of text without modifying the document content.

1 This facility is critical for providing a mechanism for providing user feedback
2 without affecting persistence, undo, etc.

3 4 **BRIEF DESCRIPTION OF THE DRAWINGS**

5 A more complete understanding of exemplary methods and arrangements
6 of the present invention may be had by reference to the following detailed
7 description when taken in conjunction with the accompanying drawings wherein:

8 Fig. 1 is an exemplary computer system on which the present invention
9 may be implemented.

10 Fig. 2 is a block diagram of a computer having an extensible editor and
11 several extensions coupled with the editor stored in memory.

12 Fig. 3 is a block diagram of an editor including a designer interface.

13 Fig. 4 is a block diagram of an event routing model utilized in an extensible
14 editor.

15 Fig. 5 is a flow diagram of an event routing model for use in an extensible
16 editor.

17 Fig. 6 is a block diagram of an editor including a selection services
18 interface.

19 Fig. 7 is a block diagram of an editor including a highlighting services
20 interface.

DETAILED DESCRIPTION

The invention is illustrated in the drawings as being implemented in a suitable computing environment. Although not required, the invention will be described in the general context of computer-executable instructions, such as program modules, to be executed by a computing device, such as a personal computer or a hand-held computer or electronic device. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the invention may be practiced with other computer system configurations, including multi-processor systems, microprocessor-based or programmable consumer electronics, network PCs, minicomputers, mainframe computers, and the like. The invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote memory storage devices.

Exemplary Computer Environment

The various components and functionality described herein are implemented with a number of individual computers. Fig. 1 shows components of typical example of such a computer, referred by to reference numeral 100. The components shown in Fig. 1 are only examples, and are not intended to suggest any limitation as to the scope of the functionality of the invention; the invention is not necessarily dependent on the features shown in Fig. 1.

1 Generally, various different general purpose or special purpose computing
2 system configurations can be used. Examples of well known computing systems,
3 environments, and/or configurations that may be suitable for use with the
4 invention include, but are not limited to, personal computers, server computers,
5 hand-held or laptop devices, multiprocessor systems, microprocessor-based
6 systems, set top boxes, programmable consumer electronics, network PCs,
7 minicomputers, mainframe computers, distributed computing environments that
8 include any of the above systems or devices, and the like.

9 The functionality of the computers is embodied in many cases by
10 computer-executable instructions, such as program modules, that are executed by
11 the computers. Generally, program modules include routines, programs, objects,
12 components, data structures, etc. that perform particular tasks or implement
13 particular abstract data types. Tasks might also be performed by remote
14 processing devices that are linked through a communications network. In a
15 distributed computing environment, program modules may be located in both local
16 and remote computer storage media.

17 The instructions and/or program modules are stored at different times in the
18 various computer-readable media that are either part of the computer or that can be
19 read by the computer. Programs are typically distributed, for example, on floppy
20 disks, CD-ROMs, DVD, or some form of communication media such as a
21 modulated signal. From there, they are installed or loaded into the secondary
22 memory of a computer. At execution, they are loaded at least partially into the
23 computer's primary electronic memory. The invention described herein includes
24 these and other various types of computer-readable media when such media
25 contain instructions programs, and/or modules for implementing the steps

described below in conjunction with a microprocessor or other data processors. The invention also includes the computer itself when programmed according to the methods and techniques described below.

For purposes of illustration, programs and other executable program components such as the operating system are illustrated herein as discrete blocks, although it is recognized that such programs and components reside at various times in different storage components of the computer, and are executed by the data processor(s) of the computer.

With reference to Fig. 1, the components of computer 100 may include, but are not limited to, a processing unit 120, a system memory 130, and a system bus 121 that couples various system components including the system memory to the processing unit 120. The system bus 121 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. By way of example, and not limitation, such architectures include Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA) bus, Enhanced ISA (EISAA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnect (PCI) bus also known as the Mezzanine bus.

Computer 100 typically includes a variety of computer-readable media. Computer-readable media can be any available media that can be accessed by computer 100 and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer-readable media may comprise computer storage media and communication media. "Computer storage media" includes both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of

information such as computer-readable instructions, data structures, program modules, or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by computer 110. Communication media typically embodies computer-readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of any of the above should also be included within the scope of computer readable media.

The system memory 130 includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) 131 and random access memory (RAM) 132. A basic input/output system 133 (BIOS), containing the basic routines that help to transfer information between elements within computer 100, such as during start-up, is typically stored in ROM 131. RAM 132 typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit 120. By way of example, and not limitation, Fig. 1 illustrates operating system 134, application programs 135, other program modules 136, and program data 137.

The computer 100 may also include other removable/non-removable, volatile/nonvolatile computer storage media. By way of example only, Fig. 1 illustrates a hard disk drive 141 that reads from or writes to non-removable, nonvolatile magnetic media, a magnetic disk drive 151 that reads from or writes to a removable, nonvolatile magnetic disk 152, and an optical disk drive 155 that reads from or writes to a removable, nonvolatile optical disk 156 such as a CD ROM or other optical media. Other removable/non-removable, volatile/nonvolatile computer storage media that can be used in the exemplary operating environment include, but are not limited to, magnetic tape cassettes, flash memory cards, digital versatile disks, digital video tape, solid state RAM, solid state ROM, and the like. The hard disk drive 141 is typically connected to the system bus 121 through a non-removable memory interface such as interface 140, and magnetic disk drive 151 and optical disk drive 155 are typically connected to the system bus 121 by a removable memory interface such as interface 150.

The drives and their associated computer storage media discussed above and illustrated in Fig. 1 provide storage of computer-readable instructions, data structures, program modules, and other data for computer 100. In Fig. 1, for example, hard disk drive 141 is illustrated as storing operating system 144, application programs 145, other program modules 146, and program data 147. Note that these components can either be the same as or different from operating system 134, application programs 135, other program modules 136, and program data 137. Operating system 144, application programs 145, other program modules 146, and program data 147 are given different numbers here to illustrate that, at a minimum, they are different copies. A user may enter commands and

1 information into the computer 100 through input devices such as a keyboard 162
2 and pointing device 161, commonly referred to as a mouse, trackball, or touch
3 pad. Other input devices (not shown) may include a microphone, joystick, game
4 pad, satellite dish, scanner, or the like. These and other input devices are often
5 connected to the processing unit 120 through a user input interface 160 that is
6 coupled to the system bus, but may be connected by other interface and bus
7 structures, such as a parallel port, game port, or a universal serial bus (USB). A
8 monitor 191 or other type of display device is also connected to the system bus
9 121 via an interface, such as a video interface 190. In addition to the monitor,
10 computers may also include other peripheral output devices such as speakers 197
11 and printer 196, which may be connected through an output peripheral interface
12 195.

13 The computer may operate in a networked environment using logical
14 connections to one or more remote computers, such as a remote computer 180.
15 The remote computer 180 may be a personal computer, a server, a router, a
16 network PC, a peer device or other common network node, and typically includes
17 many or all of the elements described above relative to computer 100, although
18 only a memory storage device 181 has been illustrated in Fig. 1. The logical
19 connections depicted in Fig. 1 include a local area network (LAN) 171 and a wide
20 area network (WAN) 173, but may also include other networks. Such networking
21 environments are commonplace in offices, enterprise-wide computer networks,
22 intranets, and the Internet.

23 When used in a LAN networking environment, the computer 100 is
24 connected to the LAN 171 through a network interface or adapter 170. When used
25 in a WAN networking environment, the computer 100 typically includes a modem

172 or other means for establishing communications over the WAN 173, such as the Internet. The modem 172, which may be internal or external, may be connected to the system bus 121 via the user input interface 160, or other appropriate mechanism. In a networked environment, program modules depicted relative to the computer 100, or portions thereof, may be stored in the remote memory storage device. By way of example, and not limitation, Fig. 1 illustrates remote application programs 185 as residing on memory device 181. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be used.

Fig. 2 is a block diagram of a computer 200 having a processor 202 and memory 204. An extensible editor 206 stored in the memory 204 includes an event routing controller 208, a designer extensibility mechanism 210, a selection services component 212, and a highlight rendering services component 214. Three designers 216, 218, 220 are also stored in the memory 204. Each of the designers 216 - 220 communicates with the editor 206 via the designer extensibility mechanism 210. Each designer 216 - 220, as shown, also communicates with the selection services component 212 and the highlight rendering component 214. It is noted, however, that a designer 216 - 220 may communicate with only the selection services component 212 or the highlight rendering component 214 or with neither. However, as will become clear in the following discussion, each designer 216 - 220 must attach to the editor 206 through the designer extensibility mechanism 210.

A designer is an editor extension that is used to extend the functionality of the editor 206 and to customize the behavior of the editor 206. While an "extension" is a generic term for a designer, the term "designer" is utilized in

1 several products of the MICROSOFT CORP., such as INTERNET EXPLORER
2 5.5, MSHTML (the HTML parsing and rendering engine of INTERNET
3 EXPLORER that displays a document with editable content), the WebBrowser
4 (ActiveX) control, etc. For purposes of the present discussion, terms specific to
5 one or more of such products will be used. For example, in the present discussion,
6 editor extensions will be referred to as designers. A reference to such a specific
7 term (*e.g.*, designer) is meant to include reference to the more generic term (*e.g.*,
8 extension).

9 The designers 216 - 220 work by intercepting events and commands
10 occurring in, or received by, the editor 206. When one or more of the designers
11 216 - 220 intercepts an event (or command), the designer can change how the
12 editor 206 handles the event. Generally, a designer is written to either supplement
13 or override the editor's behavior. Several designers may be attached to the editor
14 206 at once, thereby dynamically enabling multiple levels of custom functionality.

15 Designers offer a very powerful tool for customizing the editor 206.
16 Virtually any part of the editor's behavior can be changed. For example, designers
17 may be used to add spell checking capability to the editor 206, to add table editing
18 functionality, to add annotation or revision-tracking capability, and so on. It is
19 noted that, although only three designers 216 - 220 are shown in conjunction with
20 the editor 206, any number of designers may be connected to the editor 206.

21 The designer extensibility mechanism 210, the selection services
22 component 212, and the highlight rendering services 214 of the editor 206 shown
23 in Fig. 2 provide specific functionality to the editor 206. Each of the modules and
24 the functionality it provides will be discussed separately, in detail, below.

Designer Extensibility Mechanism

Fig. 3 is a block diagram of an editor 300 similar to the editor 206 shown in Fig. 2. The editor 300 includes a default event handler 301, an event routing controller 302 and a designer registry 303. The editor also includes an edit designer interface 304 that has several methods through which one or more designers (not shown) communicate with the editor 300. Each designer that is coupled with the editor 300 communicates with the editor 300 through the edit designer interface 304. Any coupled designer may then communicate with any other interfaces that are a part of the editor 300.

When a designer is added to the editor 300, the designer is registered in the designer registry 303. The event routing controller 302 accesses the designer registry 303 to determine the designers that are coupled into the editor 300. As will be discussed in greater detail below, the event routing controller 302 utilizes the designer registry 303 when routing events to attached designers.

The methods of the edit designer interface 304 are a translate accelerator method 306 (TranslateAccelerator), a pre-handle event method 308 (PreHandleEvent), a post-handle event method 310 (PostHandleEvent), and a post-editor event notify method 312 (PostEditorEventNotify). Each method 306 - 312 has two parameters, an event identifier 314 and an event object interface 316. In one implementation, the event identifier 314 is a value included in HTMLELEMENTEVENTS2 in mshtmdid.h, and the event object interface 316 is IHTMLEventObj, which enables a designer to obtain more extended information about the event.

The methods 306 - 312 act as callback routines whenever an event occurs in the editing environment. In other words, whenever an event occurs that is

1 detected by the editor 300, each of the methods 306 - 312 is called, in a particular
2 sequence, by the editor 300 to process the event. Processing the event may entail
3 providing an external response to the event, responding internally to the event, not
4 responding to the event, consuming the event and/or passing the event for further
5 processing (*i.e.*, not consuming the event).

6 The event routing controller 302 determines when a particular method will
7 be called. If multiple designers are registered with the editor 300 in the designer
8 registry 303, the event routing controller 302 invokes the current method on each
9 designer sequentially, in the order in which the designers were registered with the
10 editor 300. Further explanation of the event routing technique will be explained
11 below with continuing reference to the elements and reference numerals of Fig. 3.

12 Fig. 4 is a block diagram of an event routing model utilized in an extensible
13 editor. In addition to the editor 300 shown in Fig. 3, Fig. 4 includes a first
14 extension, Designer A 320, and a second extension, Designer B 330. Although
15 only two designers 320, 330 are shown, it should be understood that virtually any
16 number of designers may be added to the editor 300. The functionality of the
17 routing mechanism when using more than two designers is similar to the
18 description of the routing mechanism using the two designers 320, 330.

19 The editor 300 is designed to receive notification of an event 400. If the
20 event 400 is a key combination input by a user, then the event routing controller
21 302 routes the event to the translate accelerator method 306. The event 400 is
22 made available to a translation accelerator 306a in Designer A 320. The
23 translation accelerator 306a of Designer A 320 may or may not provide a response
24 to the event 400. If a response is provided to the event 400 by Designer A 320,
25 then Designer A 320 may consume the event 400 to prevent Designer B 330 from

1 given to the key combinations and events that will trigger actions by a designer.
2 Also, multiple designers can be strategically registered with the editor 300 to
3 avoid this situation.

4 If the event 400 is not a key combination, then the event routing controller
5 makes the event 400 available to the designers 320, 330 via the pre-handle event
6 method 308. Designer A 320 first has the opportunity to respond to the event 400.
7 If Designer A 320 is configured to respond to the event 400, then it provides an
8 appropriate response. After providing a response, Designer A 320 may either
9 consume the event 400 or pass it along.

10 If, for example, Designer A 320 is an "auto correct" designer and Designer
11 B 330 is a grammar checking designer, an event (entry of a word into the
12 document) would be routed first through the auto correct designer to determine if
13 the word should be corrected. After the word is checked (whether or not it is
14 corrected), the grammar checking designer still requires notice of the event to
15 perform its function. Therefore, Designer A 320 would act on the event but still
16 make it available to Designer B 330

17 If the event 400 is not consumed by Designer A 320, then the event 400 is
18 made available to Designer B 330. Designer B 330 has the same options of
19 reacting to the event 400 as described above for Designer A 320. This is true for
20 each subsequent designer attached to the editor 300.

21 After each designer has the opportunity to respond to the event 400 a first
22 time, the event is passed to the default event handler 301 (assuming that the event
23 400 has not been previously consumed by a designer). The default event handler
24 301 then provides the default behavior of the editor 300 in response to the event
25 400. It is noted that if no designers are attached to the editor 300, then the editor

1 300 will simply provide the default editing behavior via the default event handler
2 301.

3 After the default event handler 301 has acted on the event 400, the
4 designers 320, 330 are provided another opportunity to respond to the event 400.
5 The event 400 is made available to the designers 320, 330 through the post-handle
6 event method 310. The post-handle event processing is similar to the pre-handle
7 event processing, occurring in the sequence in which the designers 320, 330 were
8 registered with the editor 300.

9 By way of example, suppose that a developer wants to implement an “auto
10 correct” designer that listens to key strokes. The designer, in this case, should
11 receive an event after a typed character is inserted into the document (i.e.,
12 PostHandleEvent) rather than before the character is inserted. Receiving the event
13 after the default editor has inserted the character allows the designer to inspect the
14 document with the correct content, allow undo of auto-correct behavior, etc.

15 After the post-handle event processing is concluded, the event 400 is
16 processed by the default handler 301.

17 The post-editor event notify method 312 is called after the editor 300 has
18 finished its post-handling of the event 400 or when a designer 320, 330 has
19 consumed the event. In the case where the event 400 is consumed by a designer
20 320, 330 before a default action takes place and no post-handle event methods are
21 called, a post-editor event notification module 312a, 312b is invoked to give the
22 designers 320, 330 an opportunity to make a final response. For example, suppose
23 a mouse down event starts a selection in a designer that implements basic text
24 selection. If there is a mouse down event, the designer starts the selection. Now,
25 if some other designer consumes the corresponding mouse up event, the designer

1 still needs to know about the mouse up event so it can terminate the selection and
2 stop responding to mouse move events.

3 Fig. 5 is a flow diagram of the preferred implementation of the event
4 routing model described above for use in an extensible editor 300. Continuing
5 reference will be made to the elements and reference numerals of Fig. 2 – Fig. 4 in
6 the description of the flow diagram.

7 At step 500, an event 400 is received by the editor 300. The event routing
8 controller 302 determines if the event 400 is a key combination at step 502. If the
9 event is a key combination (“Yes” branch, step 502), then the key combination is
10 translated at step 504 by the designers (if they are configured to translate the
11 particular command) or by the default event handler 301 if no designer translates
12 the key combination and the editor 300 is configured to do so.

13 If the event is not a key combination (“No” branch, step 502) the editor 300
14 determines if a designer 320, 330 is attached to the editor 300 at step 508. If there
15 is not an attached designer (“No” branch, step 508), the event is processed by the
16 default event handler 301 at step 510. If, however, a designer 320, 330 is attached
17 to the editor 300 (“Yes” branch, step 508), then the event 400 is made available to
18 Designer A 320 for pre-handling at step 512. After Designer A 320 has had the
19 opportunity to act on the event 400, Designer B 330 (“Yes” branch, step 514) has
20 the event 400 made available for processing at step 512. There is no other
21 designer attached (“No” branch, step 514), so the event (if not previously
22 consumed), is passed to the default event handler 301 and processed at step 516.

23 After the event 400 is processed by the default event handler 301 of the
24 editor 300, the event is made available to Designer A 320 for processing at step
25 518. Since there is another designer (Designer B 330) (“Yes” branch, step 520),

1 the event 400 is made available to Designer B 330 for processing at step 518.
2 When there are no more designers to process the event 400 ("No" branch, step
3 520), the event is processed by the default event handler 301 at step 522.

4 It is noted that the above discussion assumes that the event 400 is not
5 consumed by the default event handler 301 or the designers 320, 330 and is
6 processed by each method of the editor 300 and the designers 320, 330. Once an
7 event is consumed, further processing of the event terminates.

8 After the event has been through the pre-handle event method 308 and the
9 post-handle event method 310, the post-editor event notification method 312 is
10 called (step 524). Unless consumed by the default event handler 310 or one of the
11 designers 320, 330, each designer 320, 330 is notified of any response to the event
12 400 from any other module as previously described.

13 **Designer Extensibility Mechanism Interfaces**

14 In addition to the edit designer interface 304 described above, the designer
15 extensibility mechanism 210 includes an edit services interface. In MSHTML, the
16 edit services interface is designated as IHTMLEditServices, used to add or remove
17 edit designers and control the current selection. Although the general descriptions
18 of the designer extensibility mechanism can be applied and implemented in any
19 extensible editor and extensions therefor, for discussion purposes, the described
20 implementation will refer to MICROSOFT MSHTML terminology to describe
21 interfaces exposed by a designer extensibility mechanism to allow extensions to be
22 couple to properly communicate with an extensible editor. Those skilled in the art
23 will appreciate the functions enabled by the described interfaces to implement
24 custom extensions for the extensible editor.

1 The following are detailed descriptions of the edit designer interface and
2 the edit services interface.

3 Edit Designer Interface (IHTMLEditDesigner)

4 The edit designer interface includes the following methods:

5 **TranslateAccelerator**

6 Description: Called by MSHTML to translate a key combination entered
7 by a user into an appropriate command.

8 Syntax:

9 HRESULT TranslateAccelerator (
10 DISPID *inEvtDispId*,
11 IHTMLEventObj **pIEventObj*

12 Parameters:

13 *inEvtDispId*

14 [in] DISPID that specifies the event.

15 *pIEventObj*

16 [in] Pointer to an IHTMLEventObj interface that specifies the
17 event.

18 Return Values:

19 Returns S_OK to indicate that the event has been completely
20 handled and that no further processing should take place, either by
21 other edit designers or the MSHTML Editor. Returns S_FALSE to
22 indicate that other edit designers and the MSHTML Editor should
23 perform their processing this event.
24
25

PreHandleEvent

Description: Called by MSHTML before the MSHTML Editor processes an event, so that the designer can provide its own event handling behavior.

Syntax:

```
HRESULT PreHandleEvent (  
    DISPID inEvtDispId,  
    IHTMLEventObj *pIEventObj
```

Parameters:

inEvtDispId

[in] DISPID that specifies the event.

pIEventObj

[in] Pointer to an IHTMLEventObj interface that specifies the event.

Return Values:

Returns S_OK to indicate that the event has been completely handled and that no further processing should take place, either by other edit designers or the MSHTML Editor. Returns S_FALSE to indicate that other edit designers and the MSHTML Editor should perform their pre-event processing.

PostHandleEvent

Description: Called by MSHTML after the MSHTML Editor processes an event, so that the designer can provide its own event handling behavior.

Syntax:

```
HRESULT PostHandleEvent (  
    DISPID inEvtDispId,  
    IHTMLEventObj *pIEventObj
```


Parameters:

inEvtDispId

[in] DISPID that specifies the event.

pIEventObj

[in] Pointer to an IHTMLEventObj interface that specifies the event.

Return Values:

Returns S_OK to indicate that the event has been completely handled and that no further processing should take place, either by other edit designers or the MSHTML Editor. Returns S_FALSE to indicate that other edit designers and the MSHTML Editor should perform their post-event processing.

PostEditorEventNotify

Description: Called by MSHTML after an event has been handled by the MSHTML Editor and any registered edit designers.

Syntax:

```
HRESULT PostHandleEvent (  
    DISPID inEvtDispId,  
    IHTMLEventObj *pIEventObj
```

Parameters:

inEvtDispId

[in] DISPID that specifies the event.

pIEventObj

[in] Pointer to an IHTMLEventObj interface that specifies the event.

Return Values:

Returns S_OK if successful, or an error value otherwise.

Edit Services Interface (IHTMLEditServices)

The edit designer interface includes the following methods:

AddDesigner

Description: Registers an IHTMLEditDesigner interface to receive event notification from the editor.

Syntax:

```
HRESULT AddDesigner (  
    IHTMLEditDesigner *pIDesigner  
);
```

Parameters:

**pIDesigner*

[in] Pointer to an IHTMLEditDesigner interface to register for event notification.

Return Values:

Returns S_OK if successful, or an error value otherwise.

GetSelectionServices

Description: Registers an IHTMLEditDesigner interface to receive event notification from the editor.

Syntax:

```
HRESULT GetSelectionServices (  
    IMarkupContainer *pIContainer
```

1 ISelectionServices ***ppSelSvc*

2);

3 Parameters:

4 **pIContainer*

5 [in] Pointer to an IMarkupContainer interface for which an
6 ISelectionServices interface is desired.

7 ***ppSelSvc*

8 [out] Address of a pointer to a variable that receives an
9 ISelectionServices interface pointer for the ISelectionServices
10 interface on the editor's selection object.

11 Return Values:

12 Returns S_OK if successful, or an error value otherwise.

13 **MoveToSelectionAnchor**

14 Description: Moves a markup pointer to the location of an anchor for the
15 current selection.

16 Syntax:

17 HRESULT MoveSelectionToAnchor (

18 IMarkupPointer **pIStartAnchorr*

19);

20 Parameters:

21 **pIStartAnchor*

22 [in] Pointer to an IMarkupPointer interface to move the
23 location of an anchor for the selection.

24 Return Values:

25 Returns S_OK if successful, or an error value otherwise.

MoveToSelectionEnd

Description: Moves markup pointer to the end of the current selection.

Syntax:

```
HRESULT MoveToSelectionEnd (  
    IMarkupPointer *pIEndAnchor  
);
```

Parameters:

**pIEndAnchor*

[in] Pointer to an IMarkupPointer interface to move to the end of the current session.

Return Values:

Returns S_OK if successful, or an error value otherwise.

RemoveDesigner

Description: Unregisters a designer from the editor.

Syntax:

```
HRESULT RemoveDesigner (  
    IHTMLEditDesigner *pIDesigner  
);
```

Parameters:

pIDesigner

[in] Pointer to the IHTMLEditDesigner interface to remove from the event notification queue.

Return Values:

Returns S_OK if successful, or an error value otherwise.

Selection Services

Selection services provides extensions a way to modify a selection process of an extensible editor to which the designers are coupled. Although the general descriptions of the selection services can be applied and implemented in any extensible editor and extensions therefor, for discussion purposes, the described implementation will refer to MICROSOFT MSHTML terminology to describe interfaces exposed by a selection services component to allow extensions to properly communicate with an extensible editor to utilize the selection services component. Those skilled in the art will appreciate the functions enabled by the described interfaces to implement custom extensions for the extensible editor.

Fig. 6 is a block diagram of an extensible editor 600 that includes a designer interface 602, an event routing mechanism 604, and a selection services component 606. The selection services component 606 includes several interfaces: a selection services interface 608 (ISelectionServices), a selection services listener interface 610 (ISelectionServiceListener), an element segment interface 612 (IElementSegment), a segment list interface 614 (ISegmentList), and a segment interface 616 (ISegment). These interfaces 608 – 616 will be discussed in greater detail, below.

The role of the selection services interfaces 608 – 616 is to provide designers or other editing extensions with the ability to modify the logical selection state. Consequently, all editing commands and services can interact with a custom selection model without having detailed knowledge of the designer that is implementing the selection.

For example, the “bold” command is able to implement the operation of making something bold without having any knowledge of the specifics of a given

1 designer. The command is only aware of what part of the document is selected,
2 and it is configured to make the selected region of the document bold.

3 Selection Service Interface (ISelectionServices)

4 The selection services interface 608 provides methods to programmatically
5 clear, add and remove segments from a selection object. The methods include an
6 add element segment method 618 (AddElementSegment), a get markup container
7 method 620 (GetMarkupContainer), a get selection services listener method 622
8 (GetSelectionServicesListener), an add segment method 624 (AddSegment), a
9 remove segment method 626 (RemoveSegment), and a set selection type method
10 628 (SetSelectionType). The following are detailed description of the available
11 selection services interface 608 methods.

12 **AddElementSegment**

13 Description: The add element segment method 618 creates an
14 IElementSegment interface for an element in a markup container and adds the
15 segment to the editable selection.

16 Syntax:

```
17 HRESULT AddElementSegment (  
18     IHTMLElement *pIElement,  
19     IElementSegment **ppIElementAdded  
20 );
```

21 Parameters:

22 **pIElement*

23 [in] Pointer to an IHTMLElement interface that specifies the
24 element to add to the selection.
25

1 ***ppISegmentAdded*

2 [out] Address of a pointer to a variable that receives an
3 IElementSegment interface pointer for the element segment
4 added to the selection environment.

5 Return Values:

6 Returns S_OK if successful, or an error value otherwise.

7 **GetMarkupContainer**

8 Description: The get markup container method 620 retrieves the markup
9 container for the current editable selection.

10 Syntax:

11 HRESULT GetMarkupContainer (
12 IMarkupContainer ***ppIContainer*
13);

14 Parameters:

15 ***ppIContainer*

16 [out] Address of a pointer to a variable that receives an
17 IMarkupContainer interface pointer to the interface for the
18 markup container that contains the current editable selection.

19 Return Values:

20 Returns S_OK if successful, or an error value otherwise.

21 **GetSelectionServicesListener**

22 Description: The get selection services listener 622 method retrieves an
23 ISelectionServicesListener interface for the current editable selection so that the
24 editor can process certain selection events.

Syntax:

```
HRESULT GetSelectionServicesListener (  
    ISelectionServicesListener **ppISelectionServicesListener  
);
```

Parameters:

***ppISelectionServicesListener*

[out] Address of a pointer to a variable that receives an ISelectionServicesListener interface pointer to the interface that the editor will use with the current editable selection.

Return Values:

Returns S_OK if successful, or an error value otherwise.

AddSegment

Description: The add segment method 624 creates an ISegment interface for the content between two markup pointers in a markup container, and adds the segment to the editable selection.

Syntax:

```
HRETURN AddSegment (  
    IMarkupPointer *pIStart,  
    IMarkupPointer *pIEnd,  
    ISegment **ppISegmentAdded  
);
```

Parameters:

**pIStart*

[in] Pointer to an IMarkupPointer interface that specifies the start point for adding the segment.

1 **pIEnd*

2 [in] Pointer to an IMarkupPointer interface that specifies the
3 end point for adding the segment.

4 ***ppISegmentAdded*

5 [out] Address of a pointer to a variable that receives an
6 ISegment interface pointer to the interface for the added
7 segment in the selection environment.

8 Return Values:

9 Returns S_OK if successful, or an error value otherwise.

10 **RemoveSegment**

11 Description: The remove segment method 626 (RemoveSegment) removes
12 a segment from the editable selection.

13 Syntax:

14 HRESULT RemoveSegment (
15 ISegment **pISegment*
16);

17 Parameters:

18 **pISegment*

19 [in] Pointer to an ISegment interface that specifies the
20 segment to remove.

21 Return Values:

22 Returns S_OK if successful, or an error value otherwise.

23 **SetSelectionType**

24 Description: The set selection type method 628 (SetSelectionType) sets the
25 selection type and clears any existing selection.

Syntax:

```
HRESULT SetSelectionType;  
    SELECTION_TYPE eType  
    ISelectionServicesListener *pIListener  
);
```

Parameters:

eType

[in] SELECTION_TYPE enumeration that specifies the type of selection to set.

**pIListener*

[in] Optional. Pointer to an ISelectionServiceListener interface specifying the interface to associate with this selection. Set to NULL if unused. NOTE: Although this parameter is optional, without this parameter, the editor will not be able to restore the selection.

Return Values:

Returns S_OK if successful, or an error value otherwise.

Element Segment Interface (IElementSegment)

The element segment interface 610 provides methods that control a fragment of HTML markup in the current editable selections that consists of a single element. The element segment interface 612 includes a get element method 630 (GetElement), an 'is primary' method 632 (IsPrimary), and a set primary method 634 (SetPrimary). To obtain an IElementSegment interface for a fragment

1 of HTML markup representing an element, the
2 ISelectionServices::AddElementSegment method is used.

3 The selection object uses element segments to mark fragments of HTML
4 markup that are whole elements, in particular control elements.

5 **GetElement**

6 Description: The get element method 612 (GetElement) retrieves the
7 element to which this segment refers.

8 **Syntax:**

9 HRESULT GetElement (
10 IHTMLElement ***ppIElement*
11);

12 **Parameters:**

13 ***ppIElement*

14 [out] Address of a pointer to a variable that receives an
15 IHTMLElement interface pointer for the interface
16 representing the element to which the segment refers.

17 **Return Values:**

18 Returns S_OK if successful, or an error value otherwise.

19 **Is Primary**

20 Description: The is primary method 632 (IsPrimary) determines whether
21 the control element represented by this segment is the primary element of a multi-
22 element selection. The primary element of a multiple selection is typically the
23 first one chosen by a user when a selection was made. The primary element
24 typically has distinctive handles that indicate it is the primary element. For
25

example, the primary element might have white handles while the other elements have black ones).

Syntax:

```
HRESULT IsPrimary (  
    BOOL *pfPrimary  
);
```

Parameters:

**pfPrimary*

[out] Pointer to a BOOL that receives TRUE if the element is the primary element, or FALSE otherwise.

Return Values:

Returns S_OK if successful, or an error value otherwise.

Set Primary

Description: The set primary method (SetPrimary) sets or unsets a control element as a primary element in a control selection. The primary element of a multiple selection is typically the first one chosen by a user when a selection was made. The primary element typically has distinctive handles that indicate it is the primary element. For example, the primary element might have white handles while the other elements have black ones).

Syntax:

```
HRESULT SetPrimary  
    BOOL fPrimary  
);
```

Parameters:

fPrimary

[in] BOOL that specifies TRUE to set the element as the primary element, or FALSE to unset it as primary.

Return Values:

Returns S_OK if successful, or an error value otherwise.

Segment Interface (ISegment)

The segment interface 616 provides a method that creates containers (segments) for fragments of HTML markup in the current editable selection. These segments can include both a range of elements and element fragments. The segment interface 616 includes a get pointers method 636 (GetPointers).

GetPoiners

Description: The get pointers method 636 (GetPointers) positions markup pointers at the start and end of the selection segment.

Syntax:

```
HRESULT GetPointers (  
    IMarkupPointer *pIStart,  
    IMarkupPointer *pIEnd  
);
```

Parameters:

pIStart

[in] Pointer to an IMarkupPointer interface that specifies the markup pointer to position at the beginning of the segment.

pIEnd

[in] Pointer to an IMarkupPointer interface that specifies the markup pointer to position at the end of the segment.

Return Values:

Returns S_OK if successful, or an error value otherwise.

Segment List Interface (ISegmentList)

The segment list interface 614 provides methods that access information about a list of the segments in the current selection. The segment list interface 614 includes a create iterator method 638 (CreateIterator), a get type method 640 (GetType), and an 'is empty' method 640 (IsEmpty).

CreateIterator

Description: The create iterator method 638 creates an ISegmentListIterator interface used for traversing the members of a segment list.

Syntax:

```
HRESULT CreateIterator (  
    ISegmentListIterator **ppIter  
);
```

Parameters:

ppIter

[out] Address of a pointer to a variable that receives an ISegmentListIterator interface pointer for the newly created ISegmentListIterator.

Return Values:

Returns S_OK if successful, or an error value otherwise.

GetType

Description: The get type method 640 retrieves the type of the selection.

Syntax:

```
HRESULT GetType (  
    SELECTION_TYPE *peType  
);
```

Parameters:

peType

[out] Pointer to a variable of type SELECTION_TYPE that receives the selection type value.

Return Values:

Returns S_OK if successful, or an error value otherwise.

IsEmpty

Description: The 'is empty' method 642 determines whether the segment list is empty.

Syntax:

```
HRESULT IsEmpty (  
    BOOL *pfEmpty  
);
```

Parameters:

pfEmpty

[out] Pointer to a variable of type BOOL that receives TRUE if the segment list is empty, or FALSE if it is not empty.

Return Values:

Returns S_OK if successful, or an error value otherwise.

Selection Services Listener Interface (ISelectionServicesListener)

The selection services listener interface 610 provides methods that the editing component of MSHTML calls whenever certain events fire for a selection object that has a registered ISelectionServicesListener interface. This interface provides processing for undo events, for selection type changes, and whenever the mouse pointer exits the scope of an element in the editable selection. An application should supply an implementation of this interface for a selection object so that the editing component of MSHTML can respond to these events. The selection services listener interface 610 includes a begin selection undo method (BeginSelectionUndo) 644, an end selection undo method 646 (EndSelectionUndo), a get type detail method 648 (GetTypeDetail), an 'on change type' method 650 (OnChangeType), and an 'on selected element exit' method 652 (OnSelectedElementExit). To register an ISelectionServicesListener interface for a particular selection object, the ISelectionServices::SetSelectionType method or ISelectionServices::OnChangeType method is used.

BeginSelectionUndo

Description: The begin selection undo method 644 is called by the editor 600 when an editing operation is beginning that may result in a change in selection after the editing operation. This method exists so that the designers may place their own units on an Undo queue so that a selection may be restored to its original state when the editing process was started.

Syntax:

HRESULT BeginSelectionUndo (VOID);

Parameters:

None.

1 Return Values:

2 Returns S_OK if successful, or an error value otherwise.

3 **EndSelectionUndo**

4 Description: The end selection undo method 644 is called by the editor 600
5 at the end of an editing operation that may result in a change in selection after the
6 editing operation. This method exists so that the designers may place their own
7 units on an Undo Queue so that a selection may be restored to its original state
8 when the editing process was started.

9 Syntax:

10 HRESULT EndSelectionUndo (VOID);

11 Parameters:

12 None.

13 Return Values:

14 Returns S_OK if successful, or an error value otherwise.

15 **GetTypeDetail**

16 Description: The get type detail method 648 is called by MSHTML to
17 obtain the name of the selection type. This method allows a host application to
18 provide the name of a selection type when implementing a custom selection
19 mechanism. MSHTML will return a value of 'undefined' if the host does not
20 implement this method.

21 Syntax:

22 HRESULT GetTypeDetail (
23 BSTR *pTypeDetail
24);

Parameters:

pTypeDetail

[out] BSTR that specifies the name of the selection type.

Return Values:

Returns S_OK if successful, or an error value otherwise.

OnChangeType

Description: The 'on change type' method 650 is called by the editor 600 when the type of a selection changes. This method is used to implement custom processing that should take place when a selection is initiated or when a selection changes type.

Syntax:

```
HRESULT OnChangeType (  
    SELECTION_TYPE eType,  
    ISelectionServicesListener *pIListener  
);
```

Parameters:

eType

[in] SELECTION_TYPE enumeration that specified the new selection type.

pIListener

[in] Optional. Pointer to an ISelectionServicesListener interface to register with the new selection. Can be set to NULL.

Return Values:

Returns S_OK if successful, or an error value otherwise.

OnSelectedElementExit

Description: The 'on selected element' exit method 652 is called by the editor 600 whenever an element that intersects selection undo is removed from the document. This method exists so that the selection can be updated by the extensible editor (either removed or adjusted).

Syntax:

```
HRESULT OnSelectedElementExit (  
    IMarkupPointer *pIElementStart,  
    IMarkupPointer *pIElementEnd,  
    IMarkupPointer *pIElementContentStart,  
    IMarkupPointer *pIElementContentEnd  
);
```

Parameters:

**pIElementStart*

[in] Pointer to an IMarkupPointer interface specifying the point just before the element's opening tag.

**pIElementEnd*

[in] Pointer to an IMarkupPointer interface specifying the point just after the element's closing tag.

**pIElementContentStart*

[in] Pointer to an IMarkupPointer interface specifying the point just after the element's opening tag.

**pIElementContentEnd*

[in] Pointer to an IMarkupPointer interface specifying the point just before the element's closing tag.

1 Return Values:

2 Returns S_OK if successful, or an error value otherwise.

3
4 **Highlight Rendering Services**

5 Highlight rendering services allows a user to modify the rendered character
6 attributes of text without modifying the document content. This facility is critical
7 for providing a mechanism for providing user feedback without modifying the
8 document content. This component is critical for providing a mechanism for
9 providing user feedback without affecting persistence, undo, etc.

10 Fig. 7 is a block diagram of an extensible editor 700 that includes a
11 designer interface 702, an event routing mechanism 704, and a highlight rendering
12 services component 706. The highlight rendering services component 706
13 includes two interfaces: a highlight services interface 708
14 (IHighlightRenderingServices), and a highlight segment interface 710
15 (IHighlightSegment). These interfaces 708, 710 will be discussed in greater detail,
16 below.

17 **Highlight Rendering Services Interface (IHighlightRenderingServices)**

18 The highlight rendering services interface 708 provides methods that enable
19 a designer to control which sections of a document are highlighted on the screen
20 and the style of highlighting. The methods include an add segment method 712
21 (AddSegment), a move segment to pointers method 714
22 (MoveSegmentToPointers), and a remove segment method 716
23 (RemoveSegment). The following are detailed description of the available
24 selection services interface 608 methods.

AddSegment

Description: The add segment method 712 creates a highlight segment for the markup between two display pointers and highlights it according to a specified rendering style.

Syntax:

```
HRESULT AddSegment (  
    IDisplayPointer *pDispPointerStart,  
    IDisplayPointer *pDispPointerEnd,  
    IHTMLRenderStyle *pIRenderStyle,  
    IHighlightSegment **ppISegment  
);
```

Parameters:

pDispPointerStart

[in] Pointer to an IDisplayPointer interface representing the start point of the segment to be highlighted.

pDispPointerEnd

[in] Pointer to an IDisplayPointer interface representing the end point of the segment to be highlighted.

pIRenderStyle

[in] Pointer to an IHTMLRenderStyle interface representing the style with which to render the specified segment.

ppISegment

[out] Address of a pointer to a variable that receives an IHighlightSegment interface pointer for the interface that

represents the highlight segment between pDispPointerStart and pDispPointerEnd.

Return Values:

Returns S_OK if successful, or an error value otherwise.

MoveSegmentToPointers

Description: The move segments to pointers method 714 redefines a highlight segment and its style.

Syntax:

```
HRESULT MoveSegmentToPointers (  
    IHighlightSegment *pISegment,  
    IDisplayPointer *pDispPointerStart,  
    IDisplayPointer *pDispPointerEnd  
);
```

Parameters:

pISegment

[in] Pointer to an IHighlightSegment interface to redefine.

pIDispPointerStart

p[in] Pointer to an IDisplayPointer interface for the new start point of the highlight segment.

pIDispPointerEnd

[in] Pointer to an IDisplayPointer interface for a new endpoint of the highlight segment.

Return Values:

Returns S_OK if successful, or an error value otherwise.

RemoveSegment

Description: The remove segment method 716 removes a highlight segment from a collection of segments that are highlighted.

Syntax:

```
HRESULT RemoveSegment (  
    IHighlightSegment *pISegment  
);
```

Parameters:

pISegment

[in] Pointer to an IHighlightSegment interface to remove.

Return Values:

Returns S_OK if successful, or an error value otherwise.

Highlight Segment Interface (IHighlightSegment)

The highlight segment interface 710 enables a user to control a highlighted section of a document. This interface does not provide any methods of its own beyond those available from its parent interface, ISegment.

Description: The highlight segment interface 710 provides type checking for the segments added or moved from the highlighted sections through the IHighlightRenderingServices interface.

Remarks: This interface does not provide any methods of its own beyond those available from its parent interface, ISegment.

Conclusion

The services described above provide an applications program interface (API) for an extensible editor (MSHTML). The interfaces and the methods associated with each interface are summarized as follows:

IHTMLEditServices

- AddDesigner
- GetSelectionServices
- MoveToSelectionAnchor
- MoveToSelectionEnd
- RemoveDesigner

IHTMLEditDesigner

- TranslateAccelerator
- PreHandleEvent
- PostHandleEvent
- PostEditorEventNotify

ISelectionServices

- AddElementSegment
- GetMarkupContainer
- GetSelectionServicesListener
- AddSegment
- RemoveSegment
- SetSelectionType

ISelectionServicesListener

- BeginSelectionUndo
- EndSelectionUndo
- GetTypeDetail
- OnChangeType
- OnSelectedElementExit

ISegmentList

- CreateIterator
- GetType
- IsEmpty

ISegment

IElementSegment

- GetElement
- IsPrimary
- SetPrimary

IHighlightRenderingServices

- AddSegment
- MoveSegmentToPointers
- RemoveSegment

IHighlightSegment

1 The interfaces can be utilized by an extension coupled with the extensible
2 editor to add new features to the editor, to augment existing features, or to override
3 the editor's default behavior. Extensions can be used to modify the editor to
4 provide customized feedback and to present a rich editing experience to a user.

5 Although details of specific implementations and embodiments are
6 described above, such details are intended to satisfy statutory disclosure
7 obligations rather than to limit the scope of the following claims. Thus, the
8 invention as defined by the claims is not limited to the specific features described
9 above. Rather, the invention is claimed in any of its forms or modifications that
10 fall within the proper scope of the appended claims, appropriately interpreted in
11 accordance with the doctrine of equivalents.
12
13
14
15
16
17
18
19
20
21
22
23
24
25

1 **CLAIMS**

2

3 1. In an electronic document editor, a highlight rendering services

4 component comprising a highlight rendering services interface that provides one

5 or more methods to enable an editor extension to highlight a section of an

6 electronic document.

7

8 2. The highlight rendering services component as recited in claim 1,

9 wherein the methods provided by the highlight rendering services interface further

10 enable the editor extension to define a style of the section highlighting.

11

12 3. The highlight rendering services component as recited in claim 1,

13 wherein the one or more methods further comprises a method to enable the editor

14 extension to create a highlight segment between two display pointers in the

15 document.

16

17 4. The highlight rendering services component as recited in claim 1,

18 wherein the one or more methods further comprises a method to enable the editor

19 extension to create a highlight segment between two display pointers in the

20 document and to highlight the segment according to a specified rendering style.

21

22 5. The highlight rendering services component as recited in claim 1,

23 wherein the one or more methods further comprises a method to enable the editor

24 extension to redefine a highlight segment.

25

1 6. The highlight rendering services component as recited in claim 1,
2 wherein the one or more methods further comprises a method to enable the editor
3 extension to redefine a style of a highlight segment.

4
5 7. The highlight rendering services component as recited in claim 1,
6 wherein the one or more methods further comprises a method to enable the editor
7 extension to remove a highlighted segment from the document.

8
9 8. The highlight rendering services component as recited in claim 1,
10 further comprising an interface to enable the editor extension to control a
11 highlighted section of a document.

12
13 9. The highlight rendering services component as recited in claim 1,
14 further comprising an interface to enable the editor extension to control one
15 highlighted section of a document from a group of highlighted sections of the
16 document.

17
18 10. A computer-readable medium having computer-executable
19 instructions for one or more interfaces that, when executed by an electronic
20 document editor on a computer, perform the following:

21 receiving parameters from a designer through a highlight rendering services
22 interface;

23 utilizing the parameters to highlight a segment of an electronic document;

24 returning values to the designer regarding the state of the highlighted
25 segment.

1
2 **11.** The computer-readable medium as recited in claim 10, wherein the
3 utilizing the parameters further comprises utilizing the parameters to define a style
4 in which the segment is highlighted.

5
6 **12.** The computer-readable medium as recited in claim 10, wherein the
7 utilizing the parameters further comprises utilizing the parameters to create a
8 highlight segment between two display pointers in the document.

9
10 **13.** The computer-readable medium as recited in claim 10, wherein the
11 utilizing the parameters further comprises utilizing the parameters to create a
12 highlight segment between two display pointers in the document and to highlight
13 the segment according to a specified rendering style.

14
15 **14.** The computer-readable medium as recited in claim 10, wherein the
16 utilizing the parameters further comprises utilizing the parameters to redefine a
17 highlighted segment in the document.

18
19 **15.** The computer-readable medium as recited in claim 10, wherein the
20 utilizing the parameters further comprises utilizing the parameters to redefine a
21 style of a highlighted segment in the document.

1 **16.** The computer-readable medium as recited in claim 10, wherein the
2 utilizing the parameters further comprises utilizing the parameters to remove a
3 highlighted segment from the document.

4
5 **17.** A method for providing highlight rendering services to one or more
6 extensions in an extensible editor, the method comprising:

7 receiving a request from an extension to utilize the highlight rendering
8 services;

9 facilitating the request by presenting a highlight rendering services interface
10 that is accessible by the extension; and

11 communicating with the extension through the highlight rendering services
12 interface to enable the extension to highlight a section of a document through the
13 editor.

14
15 **18.** The method as recited in claim 17, wherein the facilitating further
16 comprises presenting a highlight segment interface to enable the extension to
17 control a highlighted section of a document displayed by the extensible editor, and
18 wherein the communicating further comprises communicating with the extension
19 through the highlight segment interface.

20
21 **19.** The method as recited in claim 17, wherein the highlight rendering
22 service interface further comprises an add-segment method to enable the extension
23 to create a highlight segment between two display pointers in the document and to
24 define a style of the highlighting.
25

1 **20.** The method as recited in claim 17, wherein the highlight rendering
2 service interface further comprises a move-segment-to-pointers method to enable
3 the extension to create a highlight segment between two display pointers in the
4 document and to define a style of the highlighting.

5
6 **21.** The method as recited in claim 17, wherein the highlight rendering
7 service interface further comprises a remove-segment method to enable the
8 extension to remove a highlighted section from the document.

9
10 **22.** An electronic document editor stored on a computer-readable
11 medium, comprising:

12 a designer interface to transfer data between the editor and one or more
13 designers attached to the editor;

14 an event routing controller to route events received by the editor to the one
15 or more designers;

16 a highlight rendering services component that is configured to enable a
17 designer to modify rendered character attributes of document text without
18 modifying the document content.

19
20 **23.** The electronic document editor as recited in claim 22, wherein the
21 highlight rendering services component further comprises a highlight rendering
22 services interface configured to transfer data between the editor and a designer to
23 enable the designer to control which sections of the document are highlighted on
24 the screen and the style in which the highlighting appears.

1 **24.** The electronic document editor as recited in claim 23, wherein the
2 highlight rendering services interface further comprises an add-segment method to
3 create a highlight segment between two display pointers and highlight the
4 highlight segment according to a specified rendering style.

5
6 **25.** The electronic document editor as recited in claim 23, wherein the
7 highlight rendering services interface further comprises a move-segment-to-
8 pointers method to redefine a highlight segment and a style in which the highlight
9 segment is rendered.

10
11 **26.** The electronic document editor as recited in claim 23, wherein the
12 highlight rendering services interface further comprises a remove-segment method
13 to remove a highlight segment from a collection of segments that are highlighted.

14
15 **27.** The electronic document editor as recited in claim 22, wherein the
16 highlight rendering services component further comprises a highlight segment
17 interface configured to transfer data between the editor and a designer to enable
18 the designer to provide type checking for document segments added or moved
19 from highlighted sections of the document.

ABSTRACT

An extensible editor allows integration of extensions that modify the editor's default behavior and provide customized feedback to users. The editor includes interfaces through which extensions are connected to the editor and through which selection services and highlight rendering services are provided. The selection services interfaces provide a clear separation of a logical selection position in the document and the visual feedback provided for the selection, allowing extensions to be designed that provide customized selection feedback. The highlight rendering services interfaces provide an extension with the ability to augment an existing selection without modifying the actual document.

The editor also includes an event routing model that works to decrease the occurrence of conflicts between the editor and extensions and between extensions. Upon the occurrence of an event, the editor routes the event to each extension before the editor's default handling of the event occurs. When an extension responds to an event, the extension may "consume" the event by indicating to the editor not to allow further processing of the event. After an event has been pre-processed by each extension, the default editor acts on the event. The editor then routes the event to each extension again, to allow each extension to process the event after the default editor has acted. When the post-processing is completed, each extension is notified of the actions taken by the editor and by each of the other extensions.


```
graph TD; CPU[PROCESSOR 202] --- BUS; subgraph COMPUTER_200 [COMPUTER 200]; subgraph MEMORY_204 [MEMORY 204]; EDITOR_206[EDITOR 206]; EDITOR_206 --- ERC[EVENT ROUTING CONTROLLER 208]; EDITOR_206 --- DS[DESIGNER EXT. MECH. 210]; EDITOR_206 --- SSC[SELECTION SERVICES COMPONENT 212]; EDITOR_206 --- HRS[HIGHLIGHT RENDERING SERVICES 214]; end; DS --- BUS; SSC --- BUS; HRS --- BUS; end; DS --- D216[DESIGNER 216]; SSC --- D218[DESIGNER 218]; HRS --- D220[DESIGNER 220];
```

The diagram illustrates a computer system architecture. At the top level is the **COMPUTER 200**. Inside the computer, there is a **MEMORY 204** block. Within the memory, an **EDITOR 206** block is shown, which contains an **EVENT ROUTING CONTROLLER 208** and three service components: **DESIGNER EXT. MECH. 210**, **SELECTION SERVICES COMPONENT 212**, and **HIGHLIGHT RENDERING SERVICES 214**. These three components are connected to a common bus. The bus is also connected to a **PROCESSOR 202** block located outside the memory but within the computer's boundary. Below the bus, three separate **DESIGNER** blocks are shown, labeled **216**, **218**, and **220**, each connected to the bus by a vertical line.

Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

EDITOR
700

DESIGNER INTERFACE
702

EVENT ROUTING CONTROLLER
704

HIGHLIGHT SERVICES COMPONENT
706

HIGHLIGHT REND. SERVICES I/F
708

ADD SEGMENT
712

MOVE SEGMENT TO POINTERS
714

REMOVE SEGMENT
716

HIGHLIGHT SEGMENT INTERFACE
710

Fig. 7